

**MZ-DH-4544**

**Features**

- Indoor dome camera.
- 1/3 inch SONY SUPER HAD CCD.
- 540TVL High or 330TVL Standard resolution.
- Board Lens (f : 3.6mm @ F = 2.0) standard lens.



**Specifications**

Image Sensor Device	1/3 INCH SONY SUPER HAD CCD	
Description	NTSC	PAL
Total Pixels	811 (H) x 508 (V)	795 (H) x 596 (V)
Effective Pixels	768 (H) x 494 (V)	752 (H) x 582 (V)
Scanning System	2:1 interlaced 525 lines	2:1 interlaced 625 lines
Scanning Frequency	15,734KHz (H) / 59.94Hz	15,625KHz (H) / 50Hz
Shutter Speed	1/60 ~ 1/100,000 sec	1/50 ~ 1/100,000 sec
Camera Type	Indoor dome camera	
Resolution	540 TV Lines	
Video Output	VBS 1.0V p-p Composite / 75Ω	
S/N Ratio	More than 50dB (AGC Off)	
Minimum Illumination	1 Lux @2.0	
Lens	Board Lens (f : 3.6mm @ F = 2.0) standard	
White Balance	Auto	
Shutter Speed	1/60 ~ 1/100,000sec	1/50 ~ 1/100,000sec
Power Input Jack	5.5 Jack	
Operation Temperature	(-10°C ~ 50°C )	
Power Consumption	DC 12V ± 10%, 2.4 Watts	

**Dimension**

