

MZ-DH-4544

Features

- Indoor dome camera.
- 1/3 inch SONY SUPER HAD CCD.
- 540TVL High or 330TVL Standard resolution.
- Board Lens (f : 3.6mm @ F = 2.0) standard lens.



Specifications

| | | |
|-----------------------|---|--------------------------|
| Image Sensor Device | 1/3 INCH SONY SUPER HAD CCD | |
| Description | NTSC | PAL |
| Total Pixels | 811 (H) x 508 (V) | 795 (H) x 596 (V) |
| Effective Pixels | 768 (H) x 494 (V) | 752 (H) x 582 (V) |
| Scanning System | 2:1 interlaced 525 lines | 2:1 interlaced 625 lines |
| Scanning Frequency | 15,734KHz (H) / 59.94Hz | 15,625KHz (H) / 50Hz |
| Shutter Speed | 1/60 ~ 1/100,000 sec | 1/50 ~ 1/100,000 sec |
| Camera Type | Indoor dome camera | |
| Resolution | 540 TV Lines | |
| Video Output | VBS 1.0V p-p Composite / 75Ω | |
| S/N Ratio | More than 50dB (AGC Off) | |
| Minimum Illumination | 1 Lux @2.0 | |
| Lens | Board Lens (f : 3.6mm @ F = 2.0) standard | |
| White Balance | Auto | |
| Shutter Speed | 1/60 ~ 1/100,000sec | 1/50 ~ 1/100,000sec |
| Power Input Jack | 5.5 Jack | |
| Operation Temperature | (-10°C ~ 50°C) | |
| Power Consumption | DC 12V ± 10%, 2.4 Watts | |

Dimension

